

Legacy

— porcelain stoneware



CANCOS
TILE & STONE



CHARCOAL

DOMLGCHMOS22



| 2x2 mosaic |

DOMLGCH1224



| 12x24 |

DOMLGCH24



| 24x24 |

DOMLGCHBN248



| 2x48 bullnose |

DOMLGCHLIN3D



| 6.5x40 3D lineality |

DOMLGCH2448




| 24x48 |

DOMLGCH40




| 40x40 |



MŌ
NO

BEER
WINE
SPIRITS
COCKTAIL
SPARKLING



PARIS
NEW YORK
LONDON
LOS ANGELES
GREENWICH
BRISBANE
HONG KONG
LAS VEGAS



GREY

DOMLGGRMOS22



| 2x2 mosaic |

DOMLGGR1224



| 12x24 |

DOMLGGR24



| 24x24 |

DOMLGGRBN248



| 2x48 bullnose |

DOMLGRLIN3D



| 6.5x40 3D lineality |

DOMLGGR2448



| 24x48 |

DOMLGGR40



| 40x40 |



IVORY

DOMLGIVMOS22



| 2x2 mosaic |

DOMLGIV1224



| 12x24 |

DOMLGIV24



| 24x24 |

DOMLGIVBN248



| 2x48 bullnose |

DOMLGIVLIN3D



| 6.5x40 3D lineality |

DOMLGIV2448



| 24x48 |

DOMLGIV40



| 40x40 |

CUISINE



SAND

DOMLGSAMOS22



| 2x2 mosaic |

DOMLGS1224



| 12x24 |

DOMLGS24



| 24x24 |

DOMLGSABN248



| 2x48 bullnose |

DOMLGSALIN3D



| 6.5x40 3D lineality |

DOMLGS2448



| 24x48 |

DOMLGS40



| 40x40 |



SILVER

DOMLGSIMOS22



| 2x2 mosaic |

DOMLGS1224



| 12x24 |

DOMLGS124



| 24x24 |

DOMLGSIBN248



| 2x48 bullnose |

DOMLGSILIN3D



| 6.5x40 3D lineality |

DOMLGS12448



| 24x48 |

DOMLGS140



| 40x40 |

Suggested Applications

Floor Wall Residential Light Commercial Heavy Commercial Exterior Pools

*Wear can vary greatly, please consult with a professional.

Installation Suggestions

Plank Installation* Modular Setting Joint Size 2mm

*Install the offset the width of the plank. For professional installation, the use of leveling spacers for all plank and rectangular (ie. 12x24) format tiles is recommended.

EDGE: Straight/Pressed Rustic Rectified

FINISH: Matte Polished Structured Honed Semi-Polished

Porcelain Type

through-body color-bodied glazed unglazed double-loaded other

Shade Variation

V1 Uniform Appearance V2 Slight Variation V3 Moderate Variation V4 Substantial Variation

THICKNESS: 10mm 8.5mm (40")

OF FACES: 12x24: 60 24x24: 30 24x48: 15 40x40: 8 10x40: 16

Slip Resistance

DCOF **0.73**

Values	Applications
0.42	Recommended Standard DCOF value for wet/dry commercial flooring
0.65	Recommended Standard DCOF value for ADA ramps

DIN 51130 *R9: Industry Standard/ADA Requirements **R11: Recommended For Exteriors

R9* (3-10°) R10 (10-19°) R11** (19-27°) R12 (27-35°) R13 (>35°)

DIN 51097 Class	Typical Applications	Critical Angle
<input checked="" type="checkbox"/> A	Barefoot, but mainly dry aisles and walkways, dry changing areas	≥12°
<input checked="" type="checkbox"/> B	Shower rooms, pool surrounds, wet changing areas, disinfectant spray areas (plus all Class A areas)	≥18°
<input type="checkbox"/> C	Areas constantly under water, e.g. steps into pools, foot baths, inclined pool surrounds, jacuzzis (plus all Class A&B areas)	≥24°

ASTM C-1028
 ANSI A137.1
 DIN 51097/51130

Scratch Resistance

MINERAL

1. Talc (Talc)	6. Microline (Glass, Glazed Tile)
2. Gypsum (Fingernail)	7. Quartz (Unglazed Porcelain)
3. Calcite (Penny)	8. Topaz (Granite)
4. Flourite (Some Marbles)	9. Corundum (Ruby)
5. Apatite (Knife Blade)	10. Diamond (Diamond)

Industry standard ≤175mm²

MOH'S SCALE
 UNI EN ISO 10545.6

7

Wear Resistance

PEI RATING
 UNI EN ISO 10545.7

Class 1: Walls only
 Class 2: Residential floors w/minimal abrasive traffic
 Class 3: Residential interiors/light commercial traffic
 Class 4: Medium commercial applications
 Class 5: All commercial applications/heavy traffic

*Wear can vary greatly, please consult with a professional.

Stain Resistance

5: Removed after 5 minutes (hot water running)
 4: Removed by manual cleaning (weak detergent)
 3: Removed by mechanical cleaning (strong detergent)
 2: Removed by immersion (24 hrs in suitable solvent)
 1: Stain not removed

ASTM C1378-04
 UNI EN ISO 10545.14

3

Water Absorption

ASTM C-373
 UNI EN ISO 10545.3

Absorbs 0-.5% Absorbs .5-3% Absorbs 3-7% Absorbs 7% +

<input checked="" type="checkbox"/> Impervious Interior/Exterior Frost Resistant	<input type="checkbox"/> Vitreous Interior/Exterior Frost Resistant	<input type="checkbox"/> Semi-Vitreous Indoor Use Only	<input type="checkbox"/> Non-Vitreous Indoor Use Only
--	---	--	---

Breaking Strength

ASTM C648
 UNI EN ISO 10545.4

>35

Industry standard should be greater than 250 lbs or 50 N/MM²

Facial Dimension

ASTM c499-09
 UNI EN ISO 10545.02

	Standard	Tolerance	Result
flatness	±5mm	±.5%	PASS
thickness	±6mm	±.5%	PASS
straightness	±4.5mm	±.5%	PASS
squareness	±5.4mm	±.6%	PASS
sides L/W	±1.1mm / ±4.5mm	±.5%	PASS

Chemical Resistance

ASTM C650
 UNI EN ISO 10545.13

Allowances for:

	result
Acid	PASS
Bases	PASS
Chemicals	PASS

Leed Information



REQUIREMENTS FOR COMMERCIAL INTERIORS/NEW CONSTRUCTION

Sustainable Sites Site selection	1 Point
SS CREDIT 1 Heat Island Effect-non roof Material with a solar reflectant index of at least 29.	<input type="checkbox"/>
Energy & Atmosphere	1 Point
EA CREDIT 4 Green Power: Products that optimize energy performance for floors and walls using thermal conductivity. BTU-FT	<input type="checkbox"/>
Indoor Environmental Quality Low-Emitting Materials-Flooring Systems	1 Point
IEQ CREDIT 3.1-7 Green Cleaning: Reducing occupants exposure to hazardous cleaning chemicals.	<input type="checkbox"/>
IEQ CREDIT 4.1 Low Emitting Adhesives: Products less than 65 G/L VOC	<input type="checkbox"/>
IEQ CREDIT 4.3 Low Emitting Materials: Flooring systems.	<input type="checkbox"/>

Materials & Resources	1 Point	2 Points
M&R CREDIT 2 Construction Waste Management: Recycling salvaged construction waste in to new reusable materials.	50% <input type="checkbox"/>	70% <input type="checkbox"/>
M&R CREDIT 4.1-4.2 Recycled Content: The sum of post consumer plus 1/2 of the pre consumer reps at least 10-20% of total value of materials.	10% <input type="checkbox"/>	20% <input checked="" type="checkbox"/>
M&R CREDIT 5 Regional Materials: Materials manufactured within 500 miles of the project site.	10% <input type="checkbox"/>	20% <input type="checkbox"/>
Innovation in Design	1-5 Points	
ID CREDIT 1 Innovation in Design Measurable exemplary environmental performance.	<input type="checkbox"/>	

Type: **Porcelain Stoneware**

Product Line: **Legacy**

The marketing name for this product is property of Cancos Tile & Stone. This same product may be marketed under different names.