

Loudoun



*Inspired By Nature,
Made Possible By...*

CANCOS
TILE & STONE

GLASS & STONE CHEVRON & LINEALITY MOSAICS

Brilliance

Denim

Linen

Navy

Steel



GLALOBRCHEV



GLALODECHEV



GLALOLICHEV



GLALONACHEV



GLALOSTCHEV



GLALOBRLIN



GLALODELIN



GLALOLILIN



GLALONALIN



GLALOSTLIN

APPLICATION

	INTERIOR			EXTERIOR		
	R	LC	HC	R	LC	HC
Walls/Backsplashes	X	X	X			
Wet Areas*	X	X	X			
Countertops						
Submerged Areas						

R - Residential LC - Light Commercial HC - Heavy Commercial

**Can be used in wet areas/on shower walls, only if water resistant (1% or less absorption) or epoxy grout is applied*

INSTALLATION

	CB	EB*
Mortar	X	
Grout	X	X

CB - Cement Base EB - Epoxy Base

Glass Tile may be susceptible to scratching in handling and installation, as well as use. Expect variation of color from production run to production run. Please refer to the TCNA HANDBOOK for more specific information regarding installation.

SEALING & MAINTENANCE

This tile can be sealed with Stone Care International™ Penetrating Sealer, Fila MP90® sealer, or similar product. Please test on a small area before applying. Use a non-abrasive cloth and neutral detergents for cleaning. Avoid acid detergents, chemicals and solvents.

The marketing name for this product is property of Cancos Tile Corp. This same product may be marketed under different names.