

# Redwood



*Inspired By Nature,  
Made Possible By...*

**CANCOS**  
TILE & STONE

WOOD-LOOK PORCELAIN

*Aquila*



COPREAQ936



| 9 x 36 |

COPREAQMOS22



| 2 x 2 mosaic |

WOOD-LOOK PORCELAIN

Aurora



COPREAU936



| 9 x 36 |

COPREAU MOS22



| 2 x 2 mosaic |

WOOD-LOOK PORCELAIN

*Camos*



COPRECA936



| 9 x 36 |

COPRECAMOS22



| 2 x 2 mosaic |

WOOD-LOOK PORCELAIN

Nimbus



COPRENI936



| 9 x 36 |

COPRENIMOS22



| 2 x 2 mosaic |



COPRERU936




| 9 x 36 |

COPRERUMOS22



| 2 x 2 mosaic |

## Suggested Applications



## Installation Suggestions



## Porcelain Type

through-body  color-bodied  glazed  unglazed  double-loaded  other \_\_\_\_\_

## Shade Variation



## Slip Resistance

DCOF	Values	Applications
<input checked="" type="checkbox"/> .54	0.42	Recommended Standard DCOF value for wet/dry commercial flooring
<input type="checkbox"/>	0.65	Recommended Standard DCOF value for ADA ramps

DIN 51130 \*\*R9: Industry Standard/ADA Requirements \*\*R11: Recommended For Exteriors

R9\* (3-10°)  R10 (10-19°)  R11\*\* (19-27°)  
 R12 (27-35°)  R13 (>35°)

DIN 51097		
Class	Typical Applications	Critical Angle
<input checked="" type="checkbox"/> A	Barefoot, but mainly dry aisles and walkways, dry changing areas	≥12°
<input type="checkbox"/> B	Shower rooms, pool surrounds, wet changing areas, disinfectant spray areas (plus all Class A areas)	≥18°
<input type="checkbox"/> C	Areas constantly under water, e.g. steps into pools, foot baths, inclined pool surrounds, jacuzzis (plus all Class A&B areas)	≥24°

## Scratch Resistance

MOH'S SCALE  
UNI EN ISO  
10545.6

6

MINERAL	
1. Talc (Talc)	6. Microline (Glass, Glazed Tile)
2. Gypsum (Fingernail)	7. Quartz (Unglazed Porcelain)
3. Calcite (Penny)	8. Topaz (Granite)
4. Flourite (Some Marbles)	9. Corundum (Ruby)
5. Apatite (Knife Blade)	10. Diamond (Diamond)

Industry standard ≤175mm<sup>2</sup>

## Wear Resistance

PEI RATING  
UNI EN ISO  
10545.7

- Class 1: Walls only
  - Class 2: Residential floors w/minimal abrasive traffic
  - Class 3: Residential interiors/light commercial traffic
  - Class 4: Medium commercial applications
  - Class 5: All commercial applications/heavy traffic
- \*Wear can vary greatly. please consult with a professional.*

## Stain Resistance

ASTM C1378-04  
UNI EN ISO  
10545.14

4

- 5: Removed after 5 minutes (hot water running)
- 4: Removed by manual cleaning (weak detergent)
- 3: Removed by mechanical cleaning (strong detergent)
- 2: Removed by immersion (24 hrs in suitable solvent)
- 1: Stain not removed

## Water Absorption

ASTM C-373  
UNI EN ISO  
10545.3

<input checked="" type="checkbox"/>	Absorbs 0-.5%	<input type="checkbox"/>	Absorbs .5-3%	<input type="checkbox"/>	Absorbs 3-7%	<input type="checkbox"/>	Absorbs 7% +
<input checked="" type="checkbox"/>	Impervious Interior/Exterior Frost Resistant	<input type="checkbox"/>	Vitreous Interior/Exterior Frost Resistant	<input type="checkbox"/>	Semi-Vitreous Indoor Use Only	<input type="checkbox"/>	Non-Vitreous Indoor Use Only

## Breaking Strength

ASTM C648  
UNI EN ISO  
10545.4

Industry standard should be greater than 250 lbs or 50 N/MM<sup>2</sup>

## Facial Dimension

ASTM c499-09  
UNI EN ISO  
10545.02

	Standard	Tolerance	Result
flatness	±5mm	±.5%	PASS
thickness	±6mm	±.5%	PASS
straightness	±4.5mm	±.5%	PASS
squareness	±5.4mm	±.6%	PASS
sides L/W	±1.1mm ±4.5mm	±.5%	PASS

## Chemical Resistance

ASTM C650  
UNI EN ISO  
10545.13

Allowances for:  
result  
Acid  PASS  
Bases  PASS  
Chemicals  PASS

## Lead Information



REQUIREMENTS FOR COMMERCIAL INTERIORS/NEW CONSTRUCTION

<b>Sustainable Sites</b> Site selection	1 Point	<input type="checkbox"/>
<b>SS CREDIT 1</b> Heat Island Effect-non roof Material with a solar reflectant index of at least 29.		<input type="checkbox"/>
<b>Energy &amp; Atmosphere</b>	1 Point	<input type="checkbox"/>
<b>EA CREDIT 4</b> Green Power: Products that optimize energy performance for floors and walls using thermal conductivity. BTU-FT		<input type="checkbox"/>
<b>Indoor Environmental Quality</b> Low-Emitting Materials-Flooring Systems	1 Point	<input type="checkbox"/>
<b>IEQ CREDIT 3.1-7</b> Green Cleaning: Reducing occupants exposure to hazardous cleaning chemicals.		<input type="checkbox"/>
<b>IEQ CREDIT 4.1</b> Low Emitting Adhesives: Products less than 65 G/L VOC		<input type="checkbox"/>
<b>IEQ CREDIT 4.3</b> Low Emitting Materials: Flooring systems.		<input type="checkbox"/>
<b>Materials &amp; Resources</b>	1 Point	<input type="checkbox"/>
<b>M&amp;R CREDIT 2</b> Construction Waste Management: Recycling salvaged construction waste in to new reusable materials.	50%	<input type="checkbox"/>
<b>M&amp;R CREDIT 4.1-4.2</b> Recycled Content: The sum of post consumer plus 1/2 of the pre consumer reps at least 10-20% of total value of materials.	10%	<input type="checkbox"/>
<b>M&amp;R CREDIT 5</b> Regional Materials: Materials manufactured within 500 miles of the project site.	10%	<input type="checkbox"/>
<b>Innovation in Design</b>	1-5 Points	<input type="checkbox"/>
<b>ID CREDIT 1</b> Innovation in Design Measurable exemplary environmental performance.		<input type="checkbox"/>

Type: **Porcelain Stoneware**  
Product Line: **Redwood**

\*The marketing name for this product is property of Cancos Tile & Stone. This same product may be marketed under different names.\*



*\*The marketing name for this product is property of Cancos Tile Corp.  
This same product may be marketed under different names.\**